

# CELL CRANE SCALES

**Main Technical Data** 

Accuracy Standard Display

> Filtering Units

Resolution Zero Range

Tare Range

Overload Indication

Max. Safety Load

Ultimate Load **Battery Type** 

**Battery Life** 

Adapter

Operating Temperature Range

**Operating Humidity** 

Remote Controller Distance

Battery of Remote Controller

Acceleration of Gravity



According to OIML class III

30mm (1.2") 5digits LCD/LED Low, Medium or High selectable

Kilograms or Pounds selectable

2000 to 3000 divisions standard up to 15,000 available

4% F.S.

100% F.S.

100% F.S. + 9e

125% F.S. 700% F.S.

Fully sealed Lead-Acid battery, 6V/7Ah

≥70 hours

DC 9V/1000mA

- 20°C ∼ + 50°C

≤85% RH under 20℃


Max. 15m

AAA battery, 1.5V x 2

9.793, Can be regulated

## **Heat Proof Digital Crane Scale**

Model: ACR-SH



ACR

#### **Features**


- ◆Enclosure: NEMA 12/IP54 powder coated Alodined Cast Aluminum.
- ♦ Multi-weighing units: Kg, lb are selectable, kg are default unit. ♦ Multi-function operation:
- Tare, Zero, Auto zero tracking, Total, Hold, Overload warning and record, operated through infrared remote controller.

  User-friendly design:
  Large red 5 digit LED display digit height 30 mm, Battery Operated with low battery indication, Automatic turn off, power-saving function.

  Gravity regulation:
- ♦ Gravity regulation:
  The acceleration of gravity can be regulated through remote controller according to different places value.
- ♦ Multi options:
- RS-232-continuous or on demand data output, user-selectable Wireless big screen 3", 5", wireless handheld indicator 180, 380 and 580 can match with the scale, user-selectable.

#### Min Distance between Scale and High Temperature

1000 C	1200°C	1400°C	1600℃ 2.2m	
1.6m	1.8m	2m		



### **Dimensions and Specifications**

MODEL	Cap.(kg)	Resolution (kg)	A(mm)	C(mm)	H(mm)	N.W(kg)	G.W.(kg)
ACR -SH-1	1000	0.5	100	40	600	24	27
ACR -SH-2	2000	1	100	40	600	24	27
ACR -SH-3	3000	1	130	45	720	33	36
ACR -SH-5	5000	2	145	60	850	50	55
ACR .SH-10	10000	5	170	85	900	75	78
ACR SH-15	15000	5	190	85	920	80	86



ADITSAN TECHNOLOGICAL PRODUCTS Office: 102, South Ex Plaza - II, 209 Masjid Moth, New Delhi - 110049. Ph. No.: 011-26252010